



**MATERIAL RoHS COMPLIANT:**

**1.CABLE SPEC: AMPHENOL SPECTRA-STRIP (166-0099-986)**

- (1) 9 PAIRS/ 5 SINGLES
  - (a) 8 PAIRS/ 26 AWG SOLID SILVER PLATED COPPER (DATA)
  - (b) 1 PAIR/ 28 AWG SOLID TINNED COPPER (CREFOLK)
  - (c) 5 SINGLES/ 30 AWG SINGLES 30 AWG SOLID TINNED COPPER
- (2) OVERALL SHIELD <a> ALUMINIZED POLYESTER, FOIL OUT  
<b> 36 AWG TINNED COPPER BRAID, 85% MIN COVERAGE
- (3) DIAMETER: 9.3mm

- 2.ELECTRICAL:**
- (1) CAPACITANCE: 42 PF/M NOMINAC
  - (2) IMPEDANCE: 100±5 OHM (DIFFERENTIAL TDR)
  - (3) PRINT LEGEND: AMPHENOL SPECTRA-STRIP  
4X PCIe AWM STYLE 20276 VW-1 80C RoHS COMPLIANT

**3.CONNECTOR:**

P1&P2: PCI EXPRESS 4X

- (1) P.C.B: FRA. 4 LAYERS
- (2) LATCH: STAINLESS STEEL
- (3) BACKSHELL- ZINC DIE CASTING HOOD/ NICKEL PLATING
- (4) WITH EXTERNAL UNIVERSAL KEY

4.FOR 2.5G



**P/N: PCIe-x4-XX**

**Desc. : PCIe x4 - PCIe x4 cable**