

Torridon High Speed Drive Control Modules



Hot-Swap automation for SAS and SATA drives



Reduce Time to Market

Cut time to market by 20% for new products by automating manual test procedures

Reduce Capital Costs

Faster and more detailed testing with Torridon means fewer test systems are required in the lab

Reduce Human Error

Removing human intervention during tests increases consistency and results in far fewer mistakes. Test scripting provides logging and 100% repeatability

Increase Product Reliability

Advanced techniques, such as bounds testing and fault injection provide a higher level of confidence and reduced field returns

Torridon Drive Control Modules:

The industry's first automated solution for hot-swap testing. Drive Modules vastly increase the speed of testing and introduce a level of repeatability and precision that is impossible during manual tests.

Complete Automation:

Any test that requires manual intervention to pull or plug a drive can now be fully automated.

Simple Integration:

The Torridon System works with your existing automated test setup and integrate with minimal effort. A simple command set allows for easy scripting. Quarch provides full support as standard while you get started

Who Can Benefit?

- Enclosure Manufacturers
- RAID Developers
- Storage System Integrators
- Drive Qualification Labs
- Silicon Manufacturers
- Software/Driver Designers

Torridon SAS/SATA High Speed Drive Control Modules

Interface Specification

Power

- ▶ Supplied from Torridon Interface Card or Array Controller

Comms

- ▶ USART Serial - DB9
- ▶ USART Serial - RJ45(RS232D)
- ▶ USB

Drive Compatability

Sizes

- ▶ 2.5" form factor (also compatible with 3.5" drives)

Drive Connections

- ▶ SAS and keyed SATA options

Types

- ▶ HDD, SSD, Tape

Switching

Switches

- ▶ High Speed FETs
- ▶ High Current, Low insertion loss

Switched Pins

- ▶ All precharge, power and high speed SAS data pins. Vendor specific pins on request

Timing Specification

Timers

- ▶ 6 Independent timers for multi stage hot-swap

Timing resolution

- ▶ 1mS

Pin-bounce resolution

- ▶ 10uS

Pin-bounce modes

- ▶ Simple duty-cycle
- ▶ User defined 100 bit pattern

Manual Mode

- ▶ Full manual connection control for fault injection and bugged hardware generation

Line Glitching

Timing

- ▶ Glitch any line down to 50nS

Sequences

- ▶ Run glitches in sequences and PRBS patterns

Physical Dimensions

QTL1177 (2.5" Module)

- ▶ 69.1mm x 25.9mm
- ▶ Drive offset by 32mm

Support and Utilities

Phone and email support direct to the engineers as standard

'TestMonkey' GUI for rapid test prototyping, script generation and bench testing

Ordering Information

QTL1177 - 2.5" Form Factor Single units

- ▶ Ideal for bench testing, debugging and evaluation

Multiple units

- ▶ Run from a Torridon Array Controller for synchronized testing of large disk arrays

Sales

Serial Cables, LLC

8200 S. Quebec St. Ste. A-3269
Centennial, CO 80112
303.495.2320 (direct)
720.323.6231 (cell)
303.600.2076 (fax)
sales@serialcables.com
SKYPE: serialcablesco



<http://www.quarch.com>

<http://www.serialcables.com>