



P/N	LENGTH	AWG
SA-8882-HDD-.5M	500±25	HITACHI 30AWG
SA-8882-HDD-1M	1000±30	HITACHI 30AWG

**MATERIAL RoHS COMPLIANT:**

CABLE:  
 ELECTRICAL:  
 DIFFERENTIAL IMPEDANCE TDR: 100+/-5 OHMS  
 CAPACITANCE: 47 pF/m nom.  
 SKEW(within the pair-3m sample): 8 ps/m max  
 COMPONENT:  
 CONDUCTOR: 30 AWG SOLID TINNED COPPER .010" NOM. OD  
 APPROVALS:  
 UL AWM VW-1 80°C 30V, RoHS COMPLIANT, HITACHI

CONNECTOR:  
 P0: Mini SAS 4x CABLE PLUG - 26CKT CONNECTOR (SFF-8088)  
 (1) P.C.B: FR4, 4 LAYERS  
 (2) LATCH: STAINLESS STEEL  
 (3) BACKSHELL: ZINC DIE CASTING HOOD/ NICKEL PLATING  
 (4) WITH EXTERNAL UNIVERSAL KEY  
 P1~P2 SAS DRIVE CABLE RECEPTACLE (SFF-8482)  
 P3~P4 4PIN POWER MALE CONNECTOR  
 POWER CABLE: UL 1007 18AWG 80°C 300V



**P/N: SA-8882-HDD-XX Desc. : MiniSAS (SFF-8088) - HDD (SFF-8482) female, 2x**