



P/N	LENGTH	AWG
SA-8882-HDD-.5M	500±25	HITACHI 30AWG
SA-8882-HDD-1M	1000±30	HITACHI 30AWG

MATERIAL RoHS COMPLIANT:

CABLE:

- ELECTRICAL:**
 DIFFERENTIAL IMPEDANCE TDR: 100+/-5 OHMS
 CAPACITANCE: 47 pF/m nom.
 SKEW(within the pair-3m sample): 8 ps/m max
- COMPONENT:**
 CONDUCTOR: 30 AWG SOLID TINNED COPPER .010" NOM. OD
- APPROVALS:**
 UL AWM VW-1 80°C 30V, RoHS COMPLIANT, HITACHI

CONNECTOR:

- P0: Mini SAS 4x CABLE PLUG - 26CKT CONNECTOR (SFF-8088)
 (1) P.C.B: FR4, 4 LAYERS
 (2) LATCH: STAINLESS STEEL
 (3) BACKSHELL: ZINC DIE CASTING HOOD/ NICKEL PLATING
 (4) WITH EXTERNAL UNIVERSAL KEY
- P1~P2 SAS DRIVE CABLE RECEPTACLE (SFF-8482)
 P3~P4 4PIN POWER MALE CONNECTOR
 POWER CABLE: UL 1007 18AWG 80°C 300V



P/N: SA-8882-HDD-XX Desc. : MiniSAS (SFF-8088) - HDD (SFF-8482) female, 2x