



MATERIAL RoHS COMPLIANT:

CABLE:

ELECTRICAL:

DIFFERENTIAL IMPEDANCE TDR: 100+/-5 OHMS

CAPACITANCE: 47 pF/m nom.

SKEW(within the pair-3m sample): 8 ps/m max

COMPONENT:

CONDUCTOR: 30 AWG SOLID TINNED COPPER
.010" NOM. OD

APPROVALS:

UL AWM VW-1 80°C 30V, RoHS COMPLIANT, HITACHI

CONNECTOR:

P1: Mini SAS 4x CABLE PLUG - 26CKT CONNECTOR.

- (1) P.C.B: FR4, 4 LAYERS
- (2) LATCH: STAINLESS STEEL
- (3) BACKSHELL- ZINC DIE CASTING HOOD/ NICKEL PLATING
- (4) WITH EXTERNAL UNIVERSAL KEY

P2: Mini SAS 4i CABLE PLUG - 36CKT CONNECTOR.

- (1) HOOD: NYLON, UL94-V0
- (2) P.C.B: FR4, 4 LAYERS
- (3) LATCH: STAINLESS
- (4) INTERNAL, WITH NO SIDEBAND



P/N: SA-8887-XX Desc. : MiniSAS (SFF-8088) - Int. MiniSAS (SFF-8087)