


LABELLING ON BAG:



1.CABLE:

CONDUCTOR: TWO TWISTED PAIRS, 28AWG SOLID SILVER PLATED COPPER.

INSULATION: FOAM POLYOLEFIN.

PAIR: 2 SINGLES LAID FLAT AND PARALLEL.

PAIR DRAIN WIRE: 30AWG SOLID SILVER PLATED COPPER.

PAIR SHIELD: ALUMINUM/POLYESTER TAPE. ALUMINUM SIDE FACING IN, 25% OVERLAP.

INNER SHIELD: ALUMINUM/POLYESTER TAPE, ALUMINUM SIDE PACING OUT, 25% OVERLAP.

OUTER SHIELD: 38AWG TIN PLATED COPPER BRAID, 85% COVERAGE.

DIAMETER: $\phi 4.7$ mm NOMINAL. COLOR: BLACK.

PRINT LEGEND: "MADISON CABLE CORP.TYPE CL2 75°C 28AWG (UL) TurboTwin™"

DIFFERENTIAL IMPEDANCE: 100 ± 5 OHMS @TDR

FOR SAS 3G USE.

2.CONNECTOR:

P0: Mini SAS 4X CABLE PLUG – 26CKT CONNECTOR

(1) P.C.B: FR4, 4 LAYERS

(2) LATCH: STAINLESS STEEL

(3) BACKSHELL– ZINC DIE CASTING HOOD
WITH NICKEL PLATING

(4) WITH EXTERNAL UNIVERSAL KEY

P1~P4: SATA CABLE RECEPTACLE CONNECTOR
WITH METAL SHELL



P/N: SA-S7P88-XX

Desc. : SATA (4x) - MiniSAS (SFF-8088)