

SAS4x PLUG(P0) (HOST)		SATA CABLE RECEPTACLE (TARGET) (DEVICE PLUG PIN ASSIGNMENT)		
PIN	SIGNAL	REC.	PIN	SIGNAL
S1	RX0+	P4	6	TX0+
S2	RX0-		5	TX0-
S15	TX0-		3	RX0-
S16	TX0+		2	RX0+
G1-G9	SIGNAL GROUND		1,4,7	SIGNAL GROUND
S3	RX1+	P3	6	TX1+
S4	RX1-		5	TX1-
S13	TX1-		3	RX1-
S14	TX1+		2	RX1+
G1-G9	SIGNAL GROUND		1,4,7	SIGNAL GROUND
S5	RX2+	P2	6	TX2+
S6	RX2-		5	TX2-
S11	TX2-		3	RX2-
S12	TX2+		2	RX2+
G1-G9	SIGNAL GROUND		1,4,7	SIGNAL GROUND
S7	RX3+	P1	6	TX3+
S8	RX3-		5	TX3-
S9	TX3-		3	RX3-
S10	TX3+		2	RX3+
G1-G9	SIGNAL GROUND		1,4,7	SIGNAL GROUND



P/N: SA-70S7P-XX

Desc. : SAS4x (SFF-8470) - SATA (4x)

Drawings are property of Serial Cables, LLC and for information purposes only. Do Not Edit or Copy