

WIRING DIAGRAM					
Mini SAS 4i(HOST)			Mini SAS 4i(TARGET)		
plug	PIN	SIGNAL	plug	PIN	SIGNAL
P1	B17	TX3-	P2	A17	RX3-
	B16	TX3+		A16	RX3+
	B14	TX2-		A14	RX2-
	B13	TX2+		A13	RX2+
	B6	TX1-		A6	RX1-
	B5	TX1+		A5	RX1+
	B3	TX0-		A3	RX0-
	B2	TX0+		A2	RX0+
	A17	RX3-		B17	TX3-
	A16	RX3+		B16	TX3+
	A14	RX2-		B14	TX2-
	A13	RX2+		B13	TX2+
	A6	RX1-		B6	TX1-
	A5	RX1+		B5	TX1+
	A3	RX0-		B3	TX0-
	A2	RX0+		B2	TX0+
	GND GROUP			GND GROUP	
	A1,A4,A7,A12,A15,A18 B1,B4,B7,B12,B15,B18			A1,A4,A7,A12,A15,A18 B1,B4,B7,B12,B15,B18	



**P/N: SA-8787-H2T**

**Desc. : Int. MiniSAS (SFF-8087) - Int. MiniSAS (SFF-8087)**

Drawings are property of Serial Cables, LLC and for information purposes only. Do Not Edit or Copy