

WIRING DIAGRAM					
Mini SAS 4x			Mini SAS 4x		
plug	PIN	SIGNAL	plug	PIN	SIGNAL
P0	A2	RX0+	P1	B2	TX0+
	A3	RX0-		B3	TX0-
	B3	TX0-		A3	RX0-
	B2	TX0+		A2	RX0+
	A5	RX1+	P2	B2	TX0+
	A6	RX1-		B3	TX0-
	B6	TX1-		A3	RX0-
	B5	TX1+		A2	RX0+
	A8	RX2+	P3	B2	TX0+
	A9	RX2-		B3	TX0-
	B9	TX2-		A3	RX0-
	B8	TX2+		A2	RX0+
	A11	RX3+	P4	B2	TX0+
	A12	RX3-		B3	TX0-
B12	TX3-	A3		RX0-	
B11	TX3+	A2		RX0+	
GND GROUP			GND GROUP(P1,P2,P3,P4)		
A1,A4,A7,A10,A13			A1,A4,A7,A10,A13		
B1,B4,B7,B10,B13			B1,B4,B7,B10,B13		
SHELL			SHELL (P1,P2,P3,P4)		



**P/N: SA-88-88888888-XX**

**Desc. : MiniSAS (SFF-8088) - MiniSAS (SFF-8088) 4**

Drawings are property of Serial Cables, LLC and for information purposes only. Do Not Edit or Copy