

HIGH SPEED SIGNAL			
P1(Mini SAS 4x Plug)		P2(4x-Pluggable-QSFP)	
PIN	SIGNAL	PAD	SIGNAL
A6	RX1-	02	TX2n
A5	RX1+	03	TX2p
A12	RX3-	05	TX4n
A11	RX3+	06	TX4p
B8	TX2+	14	RX3p
B9	TX2-	15	RX3n
B2	TX0+	17	RX1p
B3	TX0-	18	RX1n
B6	TX1-	21	RX2n
B5	TX1+	22	RX2p
B12	TX3-	24	RX4n
B11	TX3+	25	RX4p
A8	RX2+	33	TX3p
A9	RX2-	34	TX3n
A2	RX0+	36	TX1p
A3	RX0-	37	TX1n
GND GROUP	GND	GND GROUP	GND
GND GROUP A1,A4,A7,A10,A13, B1,B4,B7,B10,B13		GND GROUP 01,04,07,13,16,19 20,23,26,32,35,38	
Connector Shell		Connector Shell	

LOW SPEED SIGNAL & POWER	
P1(4x-Pluggable-QSFP)	
PAD	SIGNAL
08	ModSelL
09	ResetL
10	VccRx
11	SCL
12	SDA
27	ModPrsL
28	IntL
29	VccTx
30	Vcc1
31	LPMode



P/N: SA-88QSFP-XX

Desc. : MiniSAS (SFF-8088) - QSFP

Drawings are property of Serial Cables, LLC and for information purposes only. Do Not Edit or Copy