

WIRING DIAGRAM										
MINI SAS 4X (P0)		SAS DRIVE CABLE REC.			4P POWER PLUG					
PIN	SIGNAL	REC.	PIN	SIGNAL	PLUG	PIN	SIGNAL			
A2	RX0+	P1	S6	TP+	P3	1	+12V			
A3	RX0-		S5	TP-						
B3	TX0-		S3	RP-						
B2	TX0+		S2	RP+						
GND GROUP	GND		S1,S4,S7	GND						
A5	RX1+		S13	TS+						
A6	RX1-		S12	TS-						
B6	TX1-		S10	RS-						
B5	TX1+		S9	RS+						
GND GROUP	GND		S8,S11,S14	GND						
			P13,P14,P15	+12V				P4	2	GND
			P10,P11,P12	GND						
			P7,P8,P9	+5V						
			P4,P5,P6	GND						
A8	RX2+	P2	S6	TP+	P4	1	+12V			
A9	RX2-		S5	TP-						
B9	TX2-		S3	RP-						
B8	TX2+		S2	RP+						
GND GROUP	GND		S1,S4,S7	GND						
A11	RX3+		S13	TS+						
A12	RX3-		S12	TS-						
B12	TX3-		S10	RS-						
B11	TX3+		S9	RS+						
GND GROUP	GND		S8,S11,S14	GND						
			P13,P14,P15	+12V				P4	2	GND
			P10,P11,P12	GND						
			P7,P8,P9	+5V						
			P4,P5,P6	GND						



P/N: SA-8882-HDD-XX

Desc. : MiniSAS (SFF-8088) - HDD (SFF-8482) female

Drawings are property of Serial Cables, LLC and for information purposes only. Do Not Edit or Copy