

WIRING DIAGRAM

MINI SAS 4X (P0)		SAS DRIVE CABLE REC.			4P POWER PLUG		
PIN	SIGNAL	REC.	PIN	SIGNAL	PLUG	PIN	SIGNAL
A2	RX0+	P1	S6	TP+	P5		
A3	RX0-		S5	TP-			
B3	TX0-		S3	RP-			
B2	TX0+		S2	RP+			
GND GROUP	GND		S1,S4,S7	GND			
			P13,P14,P15	+12V		1	+12V
			P10,11,12	GND		2	GND
			P7,P8,P9	+5V		4	+5V
		P4,P5,P6	GND	3	GND		
A5	RX1+	P2	S6	TP+	P6		
A6	RX1-		S5	TP-			
B6	TX1-		S3	RP-			
B5	TX1+		S2	RP+			
GND GROUP	GND		S1,S4,S7	GND			
			P13,P14,P15	+12V		1	+12V
			P10,11,12	GND		2	GND
			P7,P8,P9	+5V		4	+5V
		P4,P5,P6	GND	3	GND		
A8	RX2+	P3	S6	TP+	P7		
A9	RX2-		S5	TP-			
B9	TX2-		S3	RP-			
B8	TX2+		S2	RP+			
GND GROUP	GND		S1,S4,S7	GND			
			P13,P14,P15	+12V		1	+12V
			P10,11,12	GND		2	GND
			P7,P8,P9	+5V		4	+5V
		P4,P5,P6	GND	3	GND		
A11	RX3+	P4	S6	TP+	P8		
A12	RX3-		S5	TP-			
B12	TX3-		S3	RP-			
B11	TX3+		S2	RP+			
GND GROUP	GND		S1,S4,S7	GND			
			P13,P14,P15	+12V		1	+12V
			P10,11,12	GND		2	GND
			P7,P8,P9	+5V		4	+5V
		P4,P5,P6	GND	3	GND		

GND GROUP: A1,A4,A7,A10,A13
B1,B4,B7,B10,B13



P/N: SA-8882-XX

Desc. : MiniSAS (SFF-8088) - HDD, 4x (SFF-8482)

Drawings are property of SerialCables, LLC and for information purposes only. Do Not Edit or Copy