

WIRING DIAGRAM							
Mini SAS 4x			Mini SAS 4i				
plug	PIN	SIGNAL	plug	PIN	SIGNAL		
P1	A2	RX0+	P2	B2	TX0+		
	A3	RX0-		B3	TX0-		
	A5	RX1+		B5	TX1+		
	A6	RX1-		B6	TX1-		
	A8	RX2+		B13	TX2+		
	A9	RX2-		B14	TX2-		
	A11	RX3+		B16	TX3+		
	A12	RX3-		B17	TX3-		
	B2	TX0+		A2	RX0+		
	B3	TX0-		A3	RX0-		
	B5	TX1+		A5	RX1+		
	B6	TX1-		A6	RX1-		
	B8	TX2+		A13	RX2+		
	B9	TX2-		A14	RX2-		
	B11	TX3+		A16	RX3+		
	B12	TX3-		A17	RX3-		
	GND GROUP			GND GROUP			
	A1,A4,A7,A10,A13			A1,A4,A7,A12,A15,A18			
	B1,B4,B7,B10,B13			B1,B4,B7,B12,B15,B18			



P/N: SA-8887-XX

Desc. : MiniSAS (SFF-8088) - Int. MiniSAS (SFF-8088)

Drawings are property of Serial Cables, LLC and for information purposes only. Do Not Edit or Copy