


High Speed Signal					
4x-Pluggable-QSFP			SATA Cable Receptacle(Target)		
Pad	Signal		Pin	Signal	
06	TX4p		2	RX+	P4
05	TX4n		3	RX-	
24	RX4n	-	5	TX-	
25	RX4p	-	6	TX+	
GND Group	GND		1,4,7	GND	
33	TX3p		2	RX+	P3
34	TX3n		3	RX-	
15	RX3n	-	5	TX-	
14	RX3p	-	6	TX+	
GND Group	GND		1,4,7	GND	
03	TX2p		2	RX+	P2
02	TX2n		3	RX-	
21	RX2n	-	5	TX-	
22	RX2p	-	6	TX+	
GND Group	GND		1,4,7	GND	
36	TX1p		2	RX+	P1
37	TX1n		3	RX-	
18	RX1n	-	5	TX-	
17	RX1p	-	6	TX+	
GND Group	GND		1,4,7	GND	
GND Group 01,04,07,13,16,19 20,23,26,32,35,38					
Connector Shield			P1~P4 Connector Shield		

\*DC Blocking Caps on P0 Rx Side.

Low Speed Signal & Power		P0(4x-Pluggable-QSFP)	
Pad	SIGNAL		
08	ModSelL		Vcc
09	ResetL		Vcc
10	VccRx		N.C.
11	SCL		Vcc
12	SDA		Vcc
27	ModPrsL		GND
28	IntL		Vcc
29	VccTx		N.C.
30	Vcc1		Vcc
31	LPMode		N.C.



P/N: SA-B36S7P-XX

Desc. : QSFP (SFF-8436) - SATA (4x), braided

Drawings are property of Serial Cables, LLC and for information purposes only. Do Not Edit or Copy