

WIRING DIAGRAM					
Mini SAS 4x(HOST)			SATA internal cable rec.(TARGET)		
plug	PIN	SIGNAL	rec.	PIN	SIGNAL
P0	B2	TX0+	P1	2	RX0+
	B3	TX0-		3	RX0-
	A2	RX0+		6	TX0+
	A3	RX0-		5	TX0-
	GND GROUP			1,4,7	GROUND
	B5	TX1+	P2	2	RX1+
	B6	TX1-		3	RX1-
	A5	RX1+		6	TX1+
	A6	RX1-		5	TX1-
	GND GROUP			1,4,7	GROUND
	B8	TX2+	P3	2	RX2+
	B9	TX2-		3	RX2-
	A8	RX2+		6	TX2+
	A9	RX2-		5	TX2-
	GND GROUP			1,4,7	GROUND
	B11	TX3+	P4	2	RX3+
B12	TX3-	3		RX3-	
A11	RX3+	6		TX3+	
A12	RX3-	5		TX3-	
GND GROUP			1,4,7	GROUND	

GND GROUP:



P/N: SA-F88S7P-XX

Desc. : MiniSAS (SFF-8088) - 7 Pin SATA (4x) braided

Drawings are property of Serial Cables, LLC and for information purposes only. Do Not Edit or Copy