

WIRING DIAGRAM					
SATA internal cable rec.(HOST)			Mini SAS 4x(TARGET)		
rec.	PIN	SIGNAL	plug	PIN	SIGNAL
P1	6	RX0+	P0	B2	TX0+
	5	RX0-		B3	TX0-
	2	TX0+		A2	RX0+
	3	TX0-		A3	RX0-
	1,4,7	GROUND		GND GROUP	
P2	6	RX1+		B5	TX1+
	5	RX1-		B6	TX1-
	2	TX1+		A5	RX1+
	3	TX1-		A6	RX1-
	1,4,7	GROUND		GND GROUP	
P3	6	RX2+		B8	TX2+
	5	RX2-		B9	TX2-
	2	TX2+	A8	RX2+	
	3	TX2-	A9	RX2-	
	1,4,7	GROUND	GND GROUP		
P4	6	RX3+	B11	TX3+	
	5	RX3-	B12	TX3-	
	2	TX3+	A11	RX3+	
	3	TX3-	A12	RX3-	
	1,4,7	GROUND	GND GROUP		



P/N: SA-FS7P88-XX

Desc. : 7 Pin SATA (4x) - MiniSAS (SFF-8088) braided

Drawings are property of Serial Cables, LLC and for information purposes only. Do Not Edit or Copy