

1

2

3

4

5

6

7

8

DATE

DESCRIPTION OF CHANFE

REV

2023-06-25

INITIAL RELEASE

X1

NOTES:

1. ELECTRICAL AND MICHANICAL PERFORMANCE SHOULD MEET THE PCIE5.0 INDUSTRIAL STANDARD.
电气和机械特性满足PCIE5.0工业标准。

2. THE CABLE ASSEMBLY SHALL MEET BELOW IMPEDANCE REQUIREMENT:
TERMINATION AREA: 85±15%OHMS, CABLE ABSOLUTE AREA: 85±10%OHMS.
该产品满足下面阻抗特性：接触区域 **85±15%**欧姆，线材为**85±10%**欧姆。

3. THE CABLE ASSEMBLY SHOULD BE RoHS2.0 COMPLIANT.
该产品符合RoHS2.0。

4. 100% TEST FOR SHORT CIRCUIT, OPEN CIRCUIT AND DISLOCATION.
100%测试短路、断路、错位。

5. Dimensions Marked “▼” Shall Be Checked
标注“▼”的尺寸必须重点检验

6. INSULATION: 10M Ω MIN/DC 300V.
绝缘：10MΩ MIN/DC 300V。

7. CONDUCTION IMPEDANCE 5 Ω.
导通阻抗5Ω。

▼500±10

30±5 (2X)

30±5 (2X)

卷贴
ROUND WRAP

10MAX (2X)

40.60±0.25

P1

B1

A1

B11

A11

B12

A12

B49

A49

此处打UV胶固定线材

⑤ X4

①④

P2

B1

A1

B42

A42

35mm

50mm

⑦

P/N: PC15-CEMX8M-EDSFF2CF-0.5M
REV X1
DD/MMM/YY

LABEL DETAIL

serial

7	LABEL	604100070	空白 白色合成纸材质 25*50mm 耐撕, HF	1	PCS
6	UV GEL	605011715	UV胶, 型号2620B, 低介电, 50ML, HF	A/R	MM
5	POLYESTER TAPE	6050116XX	POLYESTER TAPE: T=0.12mm, BLACK, VTM-0, R2, HF	A/R	MM
4	EXPANDO TUBE	605040XXX	EXPANDO TUBE: BLACK, VW-1, HF	A/R	MM
3	CONNECTOR	7430353002	GEN-Z 2C SIR Female	1	PCS
2	CONNECTOR	TBD	X8 CEM MALE	1	PCS
1	CABLE	603010264	SAS CBL.: 30#*2C+2EAM, 镀银铜, 85Ω, VW-1, 蓝, HF, P5	A/R	MM
NO.	NAME	P/N	DESCRIPTION	QTY	UNIT

TITLE		X8 CEM Male TO GenZ 2C Female 0.5M P5				SHEET	1/2
CUSTOMER		CUSTOMER P/N	PC15-CEMX8M-EDSFF2CF-0.5M		DRAWING	Wanqiu Huang	
DWG NQ	WIPT818043827	UNIT	SCALE	REV	VIEW	CHECKED	Shili Yang
IPT P/N		mm	NONE	X1		APPROVAL	Zhiyu Chen

1

2

3

4

5

6

7

8

