


1. CABLE:
 CONDUCTOR: 30AWG 7/38 SILVER COPPER.
 INSULATION: FLUOROCARBON POLYMER.
 BRAID SHIELD: 5 ENDS 44 AWG TINNED COPPER, 92% MIN. COVERAGE.
 JACKET: FEP BLACK.
 DIAMETER: 0.052" (1.32 mm) NOMINAL.
2. CONNECTOR:
 P1: SFP+ MODULE
 (1)HOOD: ZINC DIE CASTING, NICKEL PLATING.
 (2)LATCH: PC RESIN UL94V, COLOR IN BLACK.
 (3)P.C.B.: 4 LAYERS, FR4. (SPCB-040077A)
 S1~S4: SMA PLUG*4.
3. PULL TAB: NYLON UL94V-0, COLOR WHITE.

4. LABELLING ON BAG:



SFP+(P1)		SMA(S1~S4)	
PIN	SIGNAL	LABEL INFO.	
12	RX-		RX-
13	RX+		RX+
18	TX+		TX+
19	TX-		TX-
GND			CABLE BRAID

Serial Cables, LLC

SFP+ TO SMA*4 CABLE

B-3035

SA-SFPSMAxx-4x

Justin

#

mm

11/23/10

DWG\B\3035